

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

IN RE APPLICATION OF: Hideki TAKASU

SERIAL NO: New Application

GAU:

FILED: Herewith

EXAMINER:

FOR: HIGH FREQUENCY SWITCH

**INFORMATION DISCLOSURE STATEMENT UNDER 37 CFR 1.97**

COMMISSIONER FOR PATENTS  
ALEXANDRIA, VIRGINIA 22313

SIR:

Applicant(s) wish to disclose the following information.

**REFERENCES**

- ☒ The applicant(s) wish to make of record the references listed on the attached form PTO-1449. Copies of the listed references are attached, where required, as are either statements of relevancy or any readily available English translations of pertinent portions of any non-English language references.
- ☐ A check or credit card payment form is attached in the amount required under 37 CFR §1.17(p).

**RELATED CASES**

- ☐ Attached is a list of applicant's pending application(s) or issued patent(s) which may be related to the present application. A copy of the patent(s), together with a copy of the claims and drawings of the pending application(s) is attached along with PTO 1449.
- ☐ A check or credit card payment form is attached in the amount required under 37 CFR §1.17(p).

**CERTIFICATION**


- ☐ Each item of information contained in this information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of this statement.
- ☐ No item of information contained in this information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application or, to the knowledge of the undersigned, having made reasonable inquiry, was known to any individual designated in 37 CFR §1.56(c) more than three months prior to the filing of this statement.

**DEPOSIT ACCOUNT**

- ☒ Please charge any additional fees for the papers being filed herewith and for which no check or credit card payment is enclosed herewith, or credit any overpayment to deposit account number 15-0030. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,  
MAIER & NEUSTADT, P.C.

  
Marvin J. Spivak

Registration No. 24,913

Customer Number

**22850**

Tel. (703) 413-3000  
Fax. (703) 413-2220  
(OSMMN 05/03)

C. Irvin McClelland  
Registration Number 21,124

Form PTO 1449  
(Modified)U.S. DEPARTMENT OF COMMERCE  
PATENT AND TRADEMARK OFFICEATTY DOCKET NO.  
249253US2SERIAL NO.  
New Application

## LIST OF REFERENCES CITED BY APPLICANT

APPLICANT  
Hideki TAKASUFILING DATE  
Herewith

GROUP

## U.S. PATENT DOCUMENTS

EXAMINER INITIAL		DOCUMENT NUMBER	DATE	NAME	CLASS	SUB CLASS	FILING DATE IF APPROPRIATE
	AA						
	AB						
	AC						
	AD						
	AE						
	AF						
	AG						
	AH						
	AI						
	AJ						
	AK						
	AL						
	AM						
	AN						

## FOREIGN PATENT DOCUMENTS

		DOCUMENT NUMBER	DATE	COUNTRY	TRANSLATION	
					YES	NO
	AO	6-196724	07/15/94	Japan		x
	AP					
	AQ					
	AR					
	AS					
	AT					
	AU					
	AV					

## OTHER REFERENCES (Including Author, Title, Date, Pertinent Pages, etc.)

	AW	
	AX	
	AY	
	AZ	<input type="checkbox"/> Additional References sheet(s) attached

Examiner

Date Considered

\*Examiner: Initial if reference is considered, whether or not citation is in conformance with MPEP 609; Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

DOCKET NO: 249253US2

Sheet 1 of 1

IN RE APPLICATION OF: Hideki TAKASU

SERIAL NO: New Application

FILED: Herewith

FOR: HIGH FREQUENCY SWITCH

**STATEMENT OF RELEVANCY**

**Reference AO (JP 6-196724) on Form PTO- 1449:**

This discloses a 4-pole monolithic GaAs PIN diode-switch having wide band-characteristic and small dimension, and includes two input ports, two output ports and eight PIN diodes. These eight diodes are composed of four pairs, each of two, which are connected between the respective input and output ports. In two of four pairs, cathodes are mutually connected, and on the other hand, in the other two pairs, anodes are mutually connected. Bias joint portions are formed at portions between the respective diode pairs so as to receive first common bias signal. The respective input and output ports receive second common bias signal.